

2090.0 mm

(C)

## PA12.15

## Air Compressors

Specifications

Ċ

.

3421.0 mm

2268.0 mm

## General Data

Battery isolator

General Data		Dimension
Emission Compliance Free Air Delivery Rated Operating Pressure	Stage V/T4f 15.30 m³ 12.10 bar	
Engine		<sup>*</sup>
Make Model Number of Cylinders Full load speed Power	Cummins B6.7 6.0 2000.0 RPM 173.0 kW	
Electrical Cooling Fuel Tank capacity AdBlue tank capacity	24 V Water 370.00 L 57.00 L	
Sound Level Data		(4*) 2424.0
Fully compliant to outdoor noise directive 2000/14/EC (2006)	99.0	(A*) 3421.0 mn (B) 2268.0 mn
Weights		
Weight (net) fixed/adjustable Weight (working) fixed/adjustable Weight max (ref. Dataplate) Weight on shipping support (net) Weight on shipping support (working)	2708 / 2778 kg 3077 / 3147 kg 3500 kg 2319 kg 2688 kg	
Standard Features		
Central lifting point Fuel/water separator No roadlights "Push after warm-up" button Bunded base with 110% fluids containment with central drains Document box Jockey Wheel LED CE and UK (13 pins) Diesel particulate filter Spark Arrestor	Emergency stop Steel Toolbox Low Fuel Light including fuel switch 28mm tow eye 40mm tow eye 50mm tow eye 68mm tow eye 76mm tow eye 50mm ball hitch	

## 938 705700 - 938 706999 • 2023- 9- 14 • ©2023 Bobcat EMEA - www.bobcat.com/eu Specifications are subject to change without notice - Pictures of Bobcat units may show other than standard equipment